## **ANT800 UHF Reader Antenna**




WWW.PROMAGEUROPE.COM

ANT800 UHF antenna is a perfect match for Promag UHF readers. It has a slim, compact design making it ideal for applications where space is limited. Customise frequency and cable length for flexibility in various applications.

## Also available:

UHF860 - UHF RFID Reader PCR800 - Desktop UHF Reader/Writer





## **Features:**

Up to 5 metre reading distance (depending on tag)

Circular polarisation (RHCP standard) or LHCP Linear polarisation also available (ANT800L)

Slim and compact housing for any space installation

Compatible with international UHF frequencies.

Applications: Access Control

Car Parking Logistics / Warehouse Tracking Asset Management

Reading Range	Up to 5 metres (tag dependant)	Cable	3M (N-Type to SMA) (standard or customisable)
RFID Protocol	ISO 18000-6C, EPC Class1 Gen 2	RF Connector	N-Type
Frequency Range	865~869 MHz, 902-928MHz or customisable	IP Rating	IP66
Innut Imnodonco	50 ohms	Dimensions	H25.6 x W26.6 x D3.0cm
Input Impedance	SUONINS	Temperature	Operating: -30 ~ +55°C
VSWR	1.5		Storage: -30 ~ +65°C
(Voltage Standing Wave Ratio)		Relative Humidity	10 ~ 85% non-condensing
Antenna Gain	9 dBi +/- 0.5	Safaty Approval	ROHS & REACH
Axial Ratio	Under 3dB	Safety Approval	
Power Input	10 Watts		
Polarisation	RHCP (standard) or LHCP Also available: ANT800L (Linear)		

Note: Specification is subject to change without notice.